

Radon Water Monitor Real Time Continuous

Model SSS-33M8-R — Radon

Specifications


- **Sensitivity:** 1 pCi/liter in 4 minutes; 0.1 pCi/liter in 40 minutes.
Requires use of the optional 1" thick lead shielding.
- **Range:** 0-100 μ Ci/liter – other ranges optional higher or lower.
- **Flow Rate:** Minimum - 1 ml/min -- Maximum - 100 ml/min
- **Sample Temperature:** Standard - < 80° F (liquid); (optional - to 115° F)
- **Ambient Temperature:** Detector - < 80° F (Optional - to 115° F) Readout - < 115° F
- **Lead Shielding:** 1/4" thick is standard
1" thick is optional

Dimensions, Weight, Shipping, Options

- **Dimensions:**
Detector - 4" dia x 19" Long
Readout - 10" H x 16" L x 19" W
- **Weight (Standard Unit):**
Detector Housing - 20 lbs.
Readout Housing - 40 lbs.
Shipping - 90 lbs.
- **Options:**
Higher temperature to 115° F.
Computer and/or recorder output.
Deionizer and Filter specification (SSS-33M8/D)



TECHNICAL ASSOCIATES
OVERHOFF TECHNOLOGY

DIVISIONS OF
 US NUCLEAR CORP

7051 ETON AVENUE, CANOGA PARK, CA 91303 | 818-883-7043 | F: 818-883-6103
RGOLDSTEINTA@USNUCLEARCORP.COM | TECH-ASSOCIATES.COM | USNUCLEARCORP.COM